

Centrella[®] Smart+ Bed

Meets the changing needs of healthcare facilities and delivers elevated care through optimized patient safety, enhanced patient satisfaction and advanced caregiver-focused technology.



Standard Features Available on Base Model

OPTIMIZED PATIENT SAFETY

Enhanced 3-Mode Bed Exit with Silence and Auto Reset

Motion Activated Nightlight

One-button Patient Stand Assist

Advanced SlideGuard[®] Technology

Foley Position Limit & Drainage Bag Holder

Head Angle <30° Limit Control

Trendelenburg/Reverse Trendelenburg

Dampened Emergency CPR

Integrated Patient Helper Bracket

ENHANCED PATIENT SATISFACTION

Device Storage Area

Integrated Urinal Holders

FlexAfoot[™] Powered Bed Extension

ADVANCED CAREGIVER-FOCUSED TECHNOLOGY

Graphical Caregiver Interface (GCI)[®] Touchscreen (right side)

Brake Not Set Alert

One-button Chair

Integrated Scale (kg/lbs)

Battery Backup

Four Corner Brake and Steer

Four Corner IV Pole Sockets

Integrated Restraint Holders

Lockout Controls

Built-in Line and Cord Management

WiFi Module

Smart Bed Ready (SideCom[®] Required)



Hillrom[™]

One Scalable Centrella® Platform

BASE FRAME	PACKAGE 255 OPTION	PACKAGE 355 OPTION
Standard Features (listed on front page)	Advanced Patient Pendant	Centrella max Powered Air Surface
Scalability	USB Charging	SafeView®+ System with IllumiGuide™ Siderail Handgrip
	Contact-Free, Continuous Monitoring Capable	Second Graphical Caregiver Interface (GCI)® Touchscreen
	Verbal Safety Prompts	

TECHNICAL SPECIFICATIONS

Overall width	40" (101.6 cm) or 43" (109.22 cm) (Comfort Edition)
Overall length with foot extension - Maximum (foot section extended) - Minimum (foot section retracted)	98.7" (251 cm) 86.7" (220 cm)
Bed height maximum	32.5" (83 cm)
Bed height minimum	14.5" (37 cm)
Head section inclination	0° to 65°
Thigh section inclination	0° to 25°
Foot section inclination	0° to 50°
Trendelenburg/Reverse Trendelenburg position (max)	15°
Caster size type	5" (13 cm) Central Locking System
Centrella CNT155 core Surface	35.5"W x 76"-88"L x 6"H
Centrella CNT255 pro Surface	35.5" or 38.5"W x 76"-88"L x 7"H
Centrella CNT355 max Surface	35.5" or 38.5"W x 76"-88"L x 8"H
Safe working load	650 lbs (295 kg) (includes patient weight, surface and accessories)
Patient weight range	70 – 500 lbs (32 – 227 kg)

A LA CARTE OPTIONS

OPTIMIZED PATIENT SAFETY FEATURES	Centrella max Powered Air Surface (includes Blower, Comfort Controls, Turn Assist and Focused Microclimate® Management)
	Centrella pro Surface
	Centrella core Surface
	PATIENT SAFETY APPLICATIONS
	NaviCare® Patient Safety
	Contact-Free, Continuous Monitoring
WatchCare™ Incontinence Management	
ENHANCED PATIENT SATISFACTION FEATURES	Comfort Edition 40" Width
	Patient Pendant (up to 2)
	Experience POD™ Device
	Active Nurse Call Button
Universal TV and Lighting Controls	
ADVANCED CAREGIVER-FOCUSED TECHNOLOGY FEATURES	SafeView+ System (with IllumiGuide Siderail Handgrip)
	5th Wheel Steering
	IntelliDrive® Powered Transport
	Second Graphical Caregiver Interface (GCI) Touchscreen
	Accessory Outlet
	Additional Line Management
	Obstacle Detect® System



hillrom.com

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products.